HYBRID INVERTER

ULTRA HYBRID PRO 12K 3F

INDEKS:3SSHZ9123F EAN: 5904100452279

VOLT

Features
Combines the function of an on-grid and off-grid
Easy parameters configuration via LCD touchscreen
Built-in Smart Meter and current transformers included with the inverter
Cooperation with the Ultra 5 energy storage
Short-circuit, overload and temperature protection
Computer software via USB or external WIFI remote control module included (view and control of
parameters)
Compatible with the system BMS
3-phase power supply with continuous power up to 12kW without mains power
Possibility to connect a 3-phase generator with autostart option (built-in relay)
5 operating modes: Store Mode, Load First Mode, Battery First Mode, Grid First Mode and
Advanced Mode (manual setting of the operating mode for different hours of the day)
Possibility of parallel operation of up to three inverters
Possibility of cooperation with other inverters connected to the building's electrical installation
(charging the battery with surplus energy from another inverter)

How does hybrid inverter combines the function of on-grid/off-grid?

On-grid:

In on-grid when the photovoltaic installation is connected to the user's electrical installation the hybrid inverter works like a typical on-grid inverter. It converts direct current (DC) generated by solar panels into alternating current (AC). Thanks to that we can power electrical devices in the house. Surplus energy is sent via the inverter to the power grid.

Off-grid:

In off-grid the hybrid inverter operates independently of the user's electrical installation. The energy obtained from solar panels is stored in batteries and then transferred to the connected devices we want to power.





- 1. DC switch 2. Battery input connectors
- 3. BTS terminals, BMS terminals, load monitor terminals, dry contact terminals, CAN communication terminals, USB terminal and cover
- 4. Circuit breaker of Grid
- 5. Load
- 6. Generator input 7. WiFi Interface
- 8. Ground
- 9. PV input with two MPPT



VOLT POLSKA SP. Z O.O. UL. ŚWIEMIROWSKA 3 81-877 SOPOT

Specification

Model	ULTRA HYBRID 12000	
Current power	3600W	
PV Input (DC)	Nominal DC operating voltage	550V
	Maximum DC voltage	800V
	MPPT voltage range	200-650V
	Maximum input current	13A/26A
	Number of MPPT tracker	2
	Strings per MPPT tracker	3
	Output voltage range	220/230/240V;180-280V
Inverter Output (AC)	Maximum output current	20/19,1A
	Frequency (Hz)	50/60Hz; 45-55/55-65Hz
	Grid type	3 phase
Battery	Battery voltage	48V
	Battery voltage range	40-60V
	Maximum charging currernt	240A
	Output waveform	Pure sine wave
Protections: short circuit, overload, temperature	Yes	
Maximum efficiency	97,10%	
Operating Temperature	(-)25∼60°C >45 °C	
Interfejs	RS485/CAN	
Cooling	Fans	
Dimensions	446x692x260mm	
Weight	38kg	
Gross dimensions	816x567x404mm	
Gross Weight	46kg	

WWW.VOLTPOLSKA.PL

